



### Light Duty Actuators

M-Track models are compact, completely self-contained and sealed to allow for use in small spaces without sacrificing power. Capacity/speed ratings from 25 lbs. @ 1.75 in./sec. to 165 lbs. @ 0.25 in./sec.



### K2 Rugged Duty Actuators

K2 acme screw models for severe duty applications. 115/230 volt AC or 12/24 volt DC motors. Load ratings to 2200 pounds. Stroke lengths to 24 inch standard.



### K2X Rugged Duty Actuators

K2X ball screw models for severe duty applications. 115/230 volt AC or 12/24 volt DC motors. Load ratings to 2800 pounds. Stroke lengths to 24 inches.



### S-Track Actuators

Controllable and quiet operation. 12 volt, 400 pound capacity. Up to 12 inch stroke. Programmable limit switches.



### K2RA Series Rotary Actuators

12 volt motor/gearing combination. For spout, winch and lift applications. Torque capacities to 140 inch pounds.



### Custom Actuators

Our broad range of standard actuators can be custom configured to meet specific applications including special pin to pin and stroke lengths, special end fittings, mounting brackets, paints, and lead wire lengths.



### Actuator Controls

All controls are state-of-the-art using surface mount electronic components and automated circuit board manufacturing methods. Actuator mounted or remote mountable models are available.